

Storage Tanks 80 – 175 GAL.



Standard Features:

- Porcelain enamel lined tank
- Heavy duty anode rods
- ASME construction available
- 2" of rigid foam insulation
- Baked enamel steel jacket
- 5 year limited warranty



These models exceed the minimum efficiency requirements of ASHRAE (Part of the Federally mandated Energy Policy Act (EPact)).

DIMENSIONAL INFORMATION (DIMENSIONS SHOWN IN INCHES)

| MODEL NUMBER | A | B | C | D | WATER CONNECTIONS | | APPROX. WEIGHT (LBS.) | |
|--------------|---------|---------|---------|--------|-------------------|-------------|-----------------------|----------|
| | | | | | TOP OUTLET | FRONT SIDES | STANDARD | ASME |
| | | | | | | | | |
| ST80(A) | 58-5/16 | 24-3/16 | 13-3/16 | 6-3/16 | 2 | 2 | 220 lbs. | 260 lbs. |
| ST100(A) | 46 | 32-1/4 | 12-9/16 | 5-9/16 | – | 2 | 475 lbs. | 475 lbs. |
| ST120(A) | 59-1/4 | 28-1/4 | 11-1/16 | 4-1/16 | 2 | 2 | 300 lbs. | 340 lbs. |
| ST175(A) | 67-1/4 | 32-1/4 | 12-9/16 | 5-9/16 | 2-1/2 | 2-1/2 | 600 lbs. | 600 lbs. |

TANK INFORMATION

| MODEL NUMBER | TANK CAPACITY (GALLONS) | MAXIMUM WORKING PRESSURE | |
|--------------|-------------------------|--------------------------|---------|
| | | STD. | ASME |
| ST80(A) | 80 | 150 PSI | 125 PSI |
| ST100(A) | 100 | 150 PSI | 160 PSI |
| ST120(A) | 115 | 150 PSI | 160 PSI |
| ST175(A) | 175 | 150 PSI | 150 PSI |

