

SPEAKMAN® S-3661-CA-E

Single Lever Faucet

FEATURES:

- Polished chrome plated vandal-resistant side mount single lever gooseneck lead-free faucet.
- All metal construction. Long-life ceramic cartridge.
- Adjustable temperature limit stop and flow control.
- Solid brass body.
- Vandal-resistant flow control reduces flow to 0.5 gpm (1.89 L/min).
- 8 in. deep gooseneck spout, rigid or swivel.
- Includes stainless steel braided hose connection from valve to spout.
- 3/8 in. compression inlets with male inlets.

COMPLIANCE:

- ASME A112.18.1/CSA B125.1 certified
- NSF 61 certified
- NSF 372 certified

FINISH:



PC

ADD-ON:

- 0.5 gpm Boca spray outlet & 1.5 gpm laminar flow outlet kit
- 1.2 gpm laminar flow outlet
- 1.2 gpm aerator

- A-BOLF
- A-ELF
- A-EA12



WARRANTY:

- 5 Year Limited

Architect/Engineer Approval Space:

SPEAKMAN
400 ANCHOR MILL ROAD
NEW CASTLE, DE 19720

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: OCTOBER 2017

DIMENSIONS: NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice.
 2. Inlet is 3/8" compression with male threads. Position faucet as close to the edge of the sink as possible.

