



SYMMONS[®] Visu-Temp[®] with Clear-Vue[™]
the smart choice[™]

Comfort is now in Clear-Vue[™]

The perfect shower is now right before your eyes...Introducing Symmons Visu-Temp[®] with Clear-Vue[™]. With its ergonomic design and easy to read display, Symmons Visu-Temp[®] with Clear-Vue[™] allows you to quickly set the perfect temperature for any shower or bath. Now the performance, durability and reliability millions have come to expect from Symmons is available together with Clear-Vue[™] in one stylish, contemporary package. Add to this our new invigorating Euro-Flo[™] showerheads and hand sprays and you have a shower or tub/shower system that provides an unparalleled bathing experience time after time.



Symmons Visu-Temp[®]
with Clear Vue[™]
is available in
these finishes:



Polished
Chrome

Radiance[®]
Satin Nickel
(STN)

Radiance[®]
Polished Brass
(BR5)



1-1000VT

Visu-Temp with Clear-Vue Shower Unit, 4-5000VT valve, 4-241 showerhead, 300 arm and flange.
 4-5000VT Valve only



1-2100VT

Visu-Temp with Clear-Vue Tub/Shower Unit, 4-5000VT valve, 4-458VT lever diverter, 060 tub spout, 4-241 showerhead, 300 arm and flange.



1-250VT-H401-V

Visu-Temp with Clear-Vue Shower Unit with Hand Shower, 4-5000VT valve, H401 hand shower.



1-1170VT-H401-V

Visu-Temp with Clear-Vue Shower Unit with Hand Shower, 4-5000VT valve, 4-458VT lever diverter, H401 hand shower, 4-241 showerhead, 300 arm and flange.



1-500VT-H401-V

Visu-Temp with Clear-Vue Shower Unit with Hand Shower, 4-5000VT valve, 4-458VT lever diverter, H401 hand shower.



1-3170VT-H401-V

Visu-Temp with Clear-Vue Tub/Shower Unit with Hand Shower, 4-5000VT valve, 4-460VT lever diverter, H401 hand shower, 060 tub spout, 4-241 showerhead, 300 arm and flange.

Modifications: Suffix QD: Quick-disconnect on hand spray units • Suffix VB: Elevated vacuum breaker with wall flanges in place on in-line vacuum breaker on hand spray units
 • Suffix X: Integral service stops - allows water shutoff at valve for service. Recommended for use on all multiple or commercial installations • Suffix X3/4: 3/4" valve to increase flow approximately 20% • Suffix X-CHK: Integral check stops - for use in installations where a positive shut-off device is used downstream of mixing valve

 Consult ADAAG and your local or state regulations for proper product choice and mounting locations.

